

MiniTrack™ NFC


Protocol ISO 14443 A

Operating frequency 13.56 MHz

Antenna size 14 x 31 mm / 0.6 x 1.2 inch

MiniTrack™ NFC key features

- Small rectangle inlay for contactless NFC with existing 14443 A infrastructure.
- High-performance product for item-level applications, ticketing and NFC applications.
- 384 bit / 48 byte user memory, with 7 byte serial number.



MiniTrack™ NFC

Antenna dimensions

Antenna size	14 x 31 mm / 0.55 x 1.22"
Die-cut size	18 x 36 mm / 0.71 x 1.42"
Web width	26 mm / 1.02"

Electrical specifications

IC	NXP Mifare Ultralight
Memory	384 bit / 48 byte
Operating frequency	13.56 MHz

General characteristics of inlay


Operating temperature	-25 °C to 70 °C -13 °F to 158 °F
Bending diameter (D)	> 50 mm tension max. 10 N
Static pressure (P)	<10 MPa

Delivery formats

Available formats	Wet
Adhesive - temperature	Solvent-free permanent adhesive min. -10 °C to 90 °C min. 14 °F to 194 °F
Quality	100% performance tested

Reel details

Standard reel size	2,500 inlays
--------------------	--------------



Inner core diameter 76 mm / 3 inch

Disclaimer

SMARTRAC TECHNOLOGY GROUP reserves the right to change its products and services at any time without notice. Our recommendations are based on our latest knowledge and experience. As our products are used in circumstances beyond our control, we cannot be held liable for any damage caused through their use.